



Declaration of Performance 113-64-2013	London Mosaic Restoration Ltd, Unit 6, Chiltonian Industrial Estate, Manor Lane, London, SE12 0TX, UK.
---	---

Range Unglazed 20x20cm	Product Category Group Bla EN 14411 : 2012 Annex G Dry Pressed Ceramic Tile With Water Absorption Eb < 0.5% (% by mass)
---------------------------	---

Country of Origin France	Scope / Intended Use Internal Wall Internal Floor External Wall External Floor ✓ ✓ ✓ ✓
-----------------------------	--

Characteristic	Performance	Harmonised Technical Specification
Reaction to Fire	Class A1-A1fl	96/603/EEC
Breaking Strength	3487 ± 9 N	ISO 10545-4
- Modulus of Rupture	68.6 ± 1.3 N/mm ²	ISO 10545-4
Durability		
- Internal Use	Pass	EN 14411:2012
- External Use (Freeze-Thaw)	Pass	ISO 10545-12
Thermal Shock Resistance	Pass	ISO 10545-9
Release of Dangerous Substances *		
- Lead	NPD	ISO 10545-15 (Pb)
- Cadmium	NPD	ISO 10545-15 (Cd)
Slip Resistance		
- Barefoot Ramp Test	A	DIN 51097
- Shod Ramp Test	NPD	DIN 51130
- Pendulum Test (Dry)	NPD	BS 7976-2:2002
- Pendulum Test (Wet)	NPD	BS 7976-2:2002
Bonding Strength		
- Cementitious Adhesive C2	> 0.5 N/mm ²	EN 12004:2007 4.1
- Dispersive Adhesive D2	> 1.0 N/mm ²	EN 12004:2007 4.2
Abrasion Resistance	PEI: V	ISO 10545-7
Chemical Resistance	Stable	ISO 10545-13
Stain Resistance	Pass	ISO 10545-14

* Where values are declared for 'Release of Dangerous Substances', the Notified Body information is given below:		
NB 1289	:	CERAM Research Ltd.
89/106/EEC		Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ
		Test Reference: (132447) - 10499 to (132447) - 10501 17th -31st May 2013

The product outlined herein, identified by "Range", is in conformity with the declared performances in the table above
This declaration of performance is issued under the sole responsibility of the manufacturer outlined above